

CRAFTING LEGACY


COLLECTION



TURNING SPACES INTO SINCE 1999 SUCCESS STORIES

At Lavish, we combine innovation, craftsmanship, and strict quality standards to produce exceptional ceramic tiles. Recognized globally and backed by certifications like ISO 9001:2015, ISO 14025:2006, CE, and UK CA, we've become a trusted name in over 85 countries. Our unique designs and dedication to perfection set us apart as true artisans in the tile industry.

BUILT ON THE FOUNDATION OF





WALL & FLOOR TILES

Craftsmanship is also at the heart of our brand! In a way, we don't consider ourselves manufacturers but we see ourselves as a team of skilled artisans who take great care in crafting beautiful surfaces that are unmatched, unparalleled, and unrivaled! The uniqueness of our product is reflected in our designs, colors, sizes, and finishes which are exclusive to us and different by all means! In short, "We are a breath of fresh air in a sea of sameness"!

Glazed Porcelain Tiles 30x60 | 60x60 | 80x80 60x120 | 80x160 | 100x100 120x120 | 120x180cm

Double Charged Tiles 60x60 | 60x120cm

Wooden Tiles 10x60cm | 20x120 | 30x120 20x160 | 26x160cm

Fullbody 60x60 | 60x120cm

Architectural Surfaces 30x120cm

Outdoor Tiles 30x30 | 30x60 | 60x60 | 60x90 60x120 | 20x120 | 30x120cm Ceramic Wall Tiles 25x40 | 30x60cm Subway Tiles

Thickness 07mm | 08mm | 09mm 12mm | 20mm





SUGAR COLLECT 60x60 / 60x120 (in cm)






















A grainy texture with a Color diversity is what makes the Sugar collection the most sought-after choice. Made with advanced glazing techniques, these tiles effortlessly embellish any space!





Palmi

FINISH :SUGAR SIZE : 60x60cm

AVAILABLE SIZES IN CM 60x60 | 60x120







| CHARACTERISTIC | STANDARD AS PER ISO-13006 / En14411 GROUP Bla | LAVISH VALUE | TEST METHOD | |
|---|---|---------------------------|--------------|--|
| REGULATORY PROPERTIES | | | | |
| Deviation in length & width | ± 0.5% | ± 0.3% | ISO-10545-2 | |
| Deviation in thickness | ± 5% | ± 4.0% | ISO-10545-2 | |
| Straightness in side | ± 0.5% | ± 0.1% | ISO-10545-2 | |
| Rectangularity | ± 0.5% | ± 0.1% | ISO-10545-2 | |
| Surface flatness | ± 0.5% | ± 0.2% | ISO-10545-2 | |
| Color difference | Unlterned | No change | ISO-10545-16 | |
| Glossiness | As per mfg. | Min 90 % | GLOSSO METER | |
| STRUCTURAL PROPERTIES | | | | |
| Water absorption | < 0.50% | < 0.05% | ISO-10545-3 | |
| Apparent density | > 2.0 g/cc | > 2.10 g/cc | DIN 51082 | |
| MASSIVE MECHANICAL PROPERTIES | | | | |
| Modulus of repture | Min. 35 N/mm² | Min. 40 N/mm² | ISO-10545-4 | |
| Breaking strength | Min. 1300 N | Min. 1800 N | ISO-10545-4 | |
| Impact resistance | As per mfg. | Min. 0.55 | ISO-10545-5 | |
| SURFACE MECHANICAL PROPERTIES | | | | |
| Resistance to surface abrasion (PEI RATING) | As per mfg. | Min. Class-3 | ISO-10545-7 | |
| MOH's hardness | As per mfg. | Min. 5 | EN 101 | |
| THERMO HYGROMETRIC PROPERTIES | | | | |
| Frost resistance | No damage | No damage | ISO-10545-12 | |
| Thermal shock resistance | No damage | No damage | ISO-10545-9 | |
| Moisture expansion | Nill | Nill | ISO-10545-10 | |
| Thermal expansion(COE) | Max. 9.0x10 ⁻⁶ | Max. 6.5x10⁻ ⁶ | ISO-10545-8 | |
| Crazing resistance | As per mfg. | Min. 10 Cycle | ISO-10545-11 | |
| CHEMICAL PROPERTIES | | | | |
| Chemical resistance | No damage | No damage | ISO-10545-13 | |
| Stain resistance | Min. Class 3 | Class 5 | ISO-10545-14 | |
| SAFETY PROPERTIES | | | | |
| Slip resistance | As per mfg. | > 0.40 | ISO-10545-17 | |
| Fire resistance | As per mfg. | Fireproof | N.A. | |
| Lead & Cafmium given off by glazes tiles | As per mfg. | Does not yield Pb & Cd | ISO-10545-15 | |

PACKING DETAILS

| Size | 30x60 CM | 60x60 CM | 80x80 CM | 60x120 CM | 80x160 CM | 100x100 CM | 120x120 CM | 120x180 CM |
|------------------------|--------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|
| Pieces / Box | 05 Pcs. | 04 Pcs. | 02 Pcs. |
| Area / Box | 0.9 sq. mtr. | 1.44 sq. mtr. | 1.28 sq. mtr. | 1.44 sq. mtr. | 2.56 sq. mtr. | 2.00 sq. mtr. | 2.88 sq. mtr. | 4.32 sq. mtr. |
| Weight / Box (approx*) | 17.5 kg | 27 kg | 26 kg | 29 kg | 52 kg | 40 kg | 58 kg | 90 kg |



LAVISH GRANITO PVT. LTD.

Halvad Road, At. Unchi Mandal, Dist. Morbi - 363 642 (Gujarat) India.

Cell: +91 99099 80082 | +91 99099 87126

E-mail: export@lavishceramics.com | inquiry@lavishceramics.com

Web: www.lavishceramics.com