



CRAFTING LEGACY

GVT


COLLECTION



TURNING SPACES INTO SUCCESS STORIES **SINCE 1999**

At Lavish, we combine innovation, craftsmanship, and strict quality standards to produce exceptional ceramic tiles. Recognized globally and backed by certifications like ISO 9001:2015, ISO 14025:2006, CE, and UK CA, we've become a trusted name in over 85 countries. Our unique designs and dedication to perfection set us apart as true artisans in the tile industry.

BUILT ON THE FOUNDATION OF



WALL & FLOOR TILES

Craftsmanship is also at the heart of our brand! In a way, we don't consider ourselves manufacturers but we see ourselves as a team of skilled artisans who take great care in crafting beautiful surfaces that are unmatched, unparalleled, and unrivaled! The uniqueness of our product is reflected in our designs, colors, sizes, and finishes which are exclusive to us and different by all means! In short, "We are a breath of fresh air in a sea of sameness"!

Glazed Porcelain Tiles
30x60 | 60x60 | 80x80
60x120 | 80x160 | 100x100
120x120 | 120x180cm

Wooden Tiles
10x60cm | 20x120 | 30x120
20x160 | 26x160cm

Architectural Surfaces
30x120cm

Ceramic Wall Tiles
25x40 | 30x60cm
Subway Tiles

Double Charged Tiles
60x60 | 60x120cm

Fullbody
60x60 | 60x120cm

Outdoor Tiles
30x30 | 30x60 | 60x60 | 60x90
60x120 | 20x120 | 30x120cm

Thickness
07mm | 08mm | 09mm
12mm | 20mm



SUGAR COLLECTION

60x60 | 60x120 (in cm)




A grainy texture with a Color diversity is what makes the Sugar collection the most sought-after choice. Made with advanced glazing techniques, these tiles effortlessly embellish any space!



Romania

FINISH :SUGAR
SIZE : 60x60cm



AVAILABLE SIZES IN CM
60x60 | 60x120





Dove



White

Dove

Grey


White

Romania

SUGAR
60x120cm

AVAILABLE SIZES
IN CM

60x60 | 60x120



CHARACTERISTIC	STANDARD AS PER ISO-13006 / En14411 GROUP Bla	LAVISH VALUE	TEST METHOD
REGULATORY PROPERTIES			
Deviation in length & width	± 0.5%	± 0.3%	ISO-10545-2
Deviation in thickness	± 5%	± 4.0%	ISO-10545-2
Straightness in side	± 0.5%	± 0.1%	ISO-10545-2
Rectangularity	± 0.5%	± 0.1%	ISO-10545-2
Surface flatness	± 0.5%	± 0.2%	ISO-10545-2
Color difference	Unlterned	No change	ISO-10545-16
Glossiness	As per mfg.	Min 90 %	GLOSSO METER
STRUCTURAL PROPERTIES			
Water absorption	< 0.50%	< 0.05%	ISO-10545-3
Apparent density	> 2.0 g/cc	> 2.10 g/cc	DIN 51082
MASSIVE MECHANICAL PROPERTIES			
Modulus of repture	Min. 35 N/mm ²	Min. 40 N/mm ²	ISO-10545-4
Breaking strength	Min. 1300 N	Min. 1800 N	ISO-10545-4
Impact resistance	As per mfg.	Min. 0.55	ISO-10545-5
SURFACE MECHANICAL PROPERTIES			
Resistance to surface abrasion (PEI RATING)	As per mfg.	Min. Class-3	ISO-10545-7
MOH's hardness	As per mfg.	Min. 5	EN 101
THERMO HYGROMETRIC PROPERTIES			
Frost resistance	No damage	No damage	ISO-10545-12
Thermal shock resistance	No damage	No damage	ISO-10545-9
Moisture expansion	Nill	Nill	ISO-10545-10
Thermal expansion(COE)	Max. 9.0x10 ⁻⁶	Max. 6.5x10 ⁻⁶	ISO-10545-8
Crazing resistance	As per mfg.	Min. 10 Cycle	ISO-10545-11
CHEMICAL PROPERTIES			
Chemical resistance	No damage	No damage	ISO-10545-13
Stain resistance	Min. Class 3	Class 5	ISO-10545-14
SAFETY PROPERTIES			
Slip resistance	As per mfg.	> 0.40	ISO-10545-17
Fire resistance	As per mfg.	Fireproof	N.A.
Lead & Cafmium given off by glazes tiles	As per mfg.	Does not yield Pb & Cd	ISO-10545-15

PACKING DETAILS

Size	30x60 CM	60x60 CM	80x80 CM	60x120 CM	80x160 CM	100x100 CM	120x120 CM	120x180 CM
Pieces / Box	05 Pcs.	04 Pcs.	02 Pcs.	02 Pcs.	02 Pcs.	02 Pcs.	02 Pcs.	02 Pcs.
Area / Box	0.9 sq. mtr.	1.44 sq. mtr.	1.28 sq. mtr.	1.44 sq. mtr.	2.56 sq. mtr.	2.00 sq. mtr.	2.88 sq. mtr.	4.32 sq. mtr.
Weight / Box (approx*)	17.5 kg	27 kg	26 kg	29 kg	52 kg	40 kg	58 kg	90 kg



LAVISH GRANITO PVT. LTD.

Halvad Road, At. Unchi Mandal, Dist. Morbi - 363 642 (Gujarat) India.

Cell : +91 99099 80082 | +91 99099 87126

E-mail : export@lavishceramics.com | inquiry@lavishceramics.com

Web : www.lavishceramics.com